

BARN FRAMING STANDARDS

as of 10/30/07

FOOTINGS	Pre-fabricated concrete 3,000 lb. mix (typically 12" x 24" round)
POLES	6" x 6"
DOOR POST	4" x 6"
GIRTS	2" x 4" or 2" x 6"
KNEE BRACING	4" x 6" or 2" x 6"
BOX BEAM	Three 2" x 10"s
LOFT JOIST	2" x 10", 16" or 24" o.c.
LOFT DECKING	¾" plywood tongue and groove
ROOF RAFTERS	2" x 10", 24" o.c.
ROOF SHEATHING	⅝" OSB with H-clips
ROOF SHINGLES	Architects shingle
EXTERIOR SIDING	1" x 10" Shiplap pine
VENTING	Soffit vent, ridge vent

STALL DESCRIPTION

FRONT WALL	2" x 6" Southern yellow pine tongue and groove with standard vertical grill (⅝" rod, 4" O.C., solid steel, black powder coated)
DOOR	4" x 8" Sliding door with standard grill and standard National Hardware
CENTER/BACK	2" x 6" Southern yellow pine tongue and groove (center vertical standard grill optional)
WINDOW	32" x 30" 6-lite pocket slider with horizontal standard grill

TACK AND FEED ROOM DESCRIPTION

EXTERIOR FRONT WALL	Vertical shiplap pine siding with passage door
---------------------	--

INTERIOR OPTIONS

INSULATION	Astro foil bubble insulation
WALL FINISH	Shiplap pine siding Sheetrock Southern yellow pine
FLOORING	Concrete, pressure-treated tongue and groove decking, rubber mats, clay or rubber paver bricks

OTHER OPTIONS

Cupolas, transoms, brush boxes, blanket bars, excavation, plumbing, electrical