

WOOD FRAME ARENA DESCRIPTION AND FRAMING STANDARDS

FOOTINGS	Pre-fabricated concrete 3,000 lb. mix (typ. 24" x 12" round)
POLES	6" x 8" PT (typical 16' high sidewall)
DOOR POSTS	4" x 6" PT
SKIRTS	2" x 10" pressure treated, Southern Yellow Pine
GIRTS	2" x 4" kiln-dried
ROOF SYSTEM	Wood trusses (typical 24" o.c.)
PURLINS	2" x 4" kiln dried, 24" on center (Applicable to metal roofs only)
ROOF SHEATHING	5/8" Plywood with clips and asphalt shingle or galvalume corrugated metal (Classic Rib- 29 gauge) with screws
SIDING	Shiplap pine or galvalume corrugated metal (Classic Rib - 29 gauge) with screws
VENTING	Ridge vent, soffit vent
WINDOWS	Filon/translucent panels (typically 4' height)
DOORS	Two 12' x 14' split sliders on gable ends

OPTIONS:

KICKBOARD	1" x 8" or 10" vertical Shiplap, angled or straight 2" x 6" horizontal T & G Southern Yellow Pine 4', 6' or 8' high (angled or straight, vertical) Without gates (standard)
CUPOLAS	4' x 4', 6' x 6'
WINDOWS	Operable or fixed window
SKYLIGHTS	Filone/translucent roof panels
INSULATION	Astro foil bubble insulation